



TAKEUCHI TB230 TB240 NEW GENERATION HYDRAULIC COMPACT EXCAVATOR



STANDARD EQUIPMENTS

- Computer-controlled engine; diagnostic system immediately informs operator of any error
- Auto deceleration system
- Sealed battery
- Flow rate setting for auxiliary service ports, easily adjustable on the LCD
- Hydraulic detent mode (Service port 1); for attachments requiring continuous hydraulic flow
- Proportional control (Service port 1)
- High pressure circuit for service port 3; easily engage and disengage quick coupler
- Hydraulic selector valve (two-way-two-way)
- Air breather
- Heater (CAB)
- Beacon lamp socket / switch
- ROPS/TOPS/OPG level 1

OPTIONS

- [COMFORT AND RELIABILITY]**
 - Air conditioner (TB240)
 - Operator's headrest
 - Cab rain guard
 - Air cleaner (Double element type)
- [OPTIONAL SAFETY DEVICES]**
 - Cab guard Roof / Front: OPG level 2)
 - ROPS / TOPS / OPG level 2)
 - Boom Swing Stopper - For wide buckets
 - Holding valves (Boom / Arm)
 - Accumulator
 - Additional front lights (CAB)
- [ADDITIONAL OPERATING DEVICES]**
 - Steed crawlers
 - Swing arm (TB230: 1,45mm/TB240: 1,409mm)
 - Swing arm valve (ISO-SG) 2way lower
 - Service ports 2, 3 & 4 - For greater attachment versatility
 - Auto pressure release - For operations requiring frequent change of attachments
 - Auto tank
 - (Auxiliary one-way circuit switch: For hydraulic brakes)
 - Angle dozer blades
 - Front Macerator
 - Automatic fuel transfer pump

BRAND NEW CABS

- [STANDARD]
 - Ergonomically designed seats (fabric/vinyl); absorbs vibration minimizing operator fatigue
 - Most switches directly accessible from the armrests
 - Rear view mirrors; displays check & monitor all the settings at once
 - Sun shade
 - (CAB: brand new standard)



CANOPY



CABIN



TAKEUCHI ADVANTAGES

- COMPACT BODIES
- HIGH-POWER ENGINES
 - Total displacement: 1,642ml (TB230); 2,190ml (TB240)
 - Engines compliant to Tier 4 Final (US) - TB230 - TB240 (DPE edition)
 - Same as the TB240 (Non-OPT Edition)
- FAST TRAVEL SPEEDS
- AUTOMATIC SHIFT DOWN
 - Travel speed TB230: 2.9km/h (1st); 5.3km/h (2nd)
 - TB240: 2.9km/h (1st); 5.3km/h (2nd)

LARGE WIDE-OPENING COVERS

- Accessible to all the vital components - Without any tool



TB228: 1,580mm → TB230: 1,655mm + 4.7% ↑
TB235: 1,600mm → TB240: 1,760mm + 10% ↑
(Above ground level)

